

Tel: 714.434.6904 Fax: 800.362.0002

Web: www.eholovision.com

BIOMETRIC ENTRY SYSTEM with KEYPAD



MODEL 426 ENTRY SYSTEM - KEYPAD AND BIOMETRIC

- Features **ekey** fingerprint keyless access systems
- · Fingerprint enrollment is at door scanner for all units
- "Draw bridge" type hinges hold unit in horizontal position for easy service
- Tamper switch output can be connected to alarm system
- Face plate dimensions: 8.125" x 5.125" (h w)
- Back box dimensions: 7.25" x 4.25" x 4.25" (h w d)

Options: Brushed stainless steel

Specify keypad type desired: Serial ASCII output
 426-A

Stand-alone 12 button 426-S12 26 Bit Wiegand output 426-W

MODEL 426-X-Z-PAN2 Includes KX-T7775 module.

MODEL 426-X-Z-TES2 - Includes TES2 intercom and relay

MODEL 426-X-Z-VIK* - High performance version using **Viking** components.

NOTE: The descriptions shown above are for the Model 426 basic unit, which includes the faceplate, keypad, rough-in box, and communication system. Add in the biometric access system from these choices:

Stand-Alone system - 1 relay
Stand-Alone system - 3 relay
Network System - 3 relay
Network System - Crestron version
Network System - Wiegand version
NS C
Network System - Wiegand version
NS W

MODEL 426-X-ZVIO2 VoIP intercom
module.

NOTE: The "X" in the part numbers above is to specify the keypad type. See above for keypad options.

NOTE: The "Z" in the part numbers above is to specify the biometric system. See above for biometric options.